

ECO PLANET CIRCULAR

ES

Montaje: Adosado / Suspendido.
(Incluidos accesorios de suspensión y adosar).

Fuente de luz: Módulos lineales LED SMD.
Temperatura de color 4000K.

Sistema óptico: Difusor.

Distribución luminosa: Directa.

Equipo eléctrico: Equipo de control electrónico. PF>0,95.
Disponibile, regulable 1-10V o DALI y/o Kit de emergencia (1 h).

Materiales: Cuerpo: Aluminio extruido lacado en blanco. Marco: Aluminio extruido lacado en blanco. Difusor: Plancha de diseño profesional (Mitsubishi LGP 4mm) con puntos.

Acabado: Color blanco.



EN

Mounting: Surface / Suspended. (Included suspended and surface accessories).

Light source: LED linear modules SMD.
Temperature color 4000K.

Optical system: Diffuser.

Light distribution: Direct.


Electrical equipment: Electronic control gear. PF>0,95.
Disponibile, dimmable 1-10V or DALI, and/or emergency Kit (1 h).

Materials: Body: Aluminum extruded lacquered in white. Frame: Extruded aluminum lacquered in white. Diffuser: Professional designed plate (Mitsubishi LGP 4mm) with points.


Surface finish: White color.




ECO PLANET CIRCULAR 35W




BAJO CONSULTA VERSION PARA EMPOTRAR
RECESSED VERSION UNDER REQUEST



ESTANDAR/STANDARD



DISPONIBLE/AVAILABLE



CONFIGURACION ONLINE ONLINE CONFIGURATION



Código Code	Referencia Reference	Kg Kg	Potencia Power	Lúmenes Lumens	Eficiencia Efficiency	CCT (K) CCT (K)
EPC123K3B	ECO PLANET CIRCULAR 35W-3350lm/840	3,0	35W	3350	96 lm/W	4000

ACCESORIOS DISPONIBLES/AVAILABLE ACCESSORIES

REGULACION/DIMMING 1-10V | DALI KIT DE EMERGENCIA/EMERGENCY KIT 1h